

PROFESSIONAL REFRIGERATION FOR THE PERFECT KITCHEN



Chill with Elan



D3 (Blast Freezer)



CBR - 2 (Flexi Drawer)



Salad, Prep & Under Counters - Static & Frost Free Series



EPS 200



Salad Under Counter ES 900

**Available
in Static or
Ventilated**



EGN 3V

Key Features:

- Easy to clean 304 grade stainless steel interior and exterior
- A unique, hinged night cover in pure stainless steel for food safety
- Static cooling models are with fan for uniform cooling
- Self closing door
- Removable gasket
- Digital temperature display



EVRX 1200 / EVRX 1400



Frost Top 3F



ESH 3000

Technical Specifications

Model	Description	Capacity (Ltrs)	Dimension (W x D x H Inch)	Temperature Range	No. of Shelves/Pans*
ES 900	2 Door Salad Under Counter / Solid Top	240	36 x 28 x 34	2°C ~ 10°C	2
ES 903	3 Door Salad Under Counter / Solid Top	360	54 x 28 x 34	2°C ~ 8°C	3
EPS 200	2 Door Under Counter with Prep Table	240	36 x 28 x 38	2°C ~ 8°C	5 x GN 1/6
EPS 300	3 Door Under Counter with Prep Table	360	54 x 28 x 38	2°C ~ 8°C	8 x GN 1/6
ESH 2000	2 Door Under Counter with Prep Table	337	60 x 32 x 42	2°C ~ 8°C	6 x GN 1/3
ESH 3000	3 Door Under Counter with Prep Table	497	80 x 32 x 42	2°C ~ 8°C	10 x GN 1/3
Frost Top 3F	Frost Top	NA	44 x 27 x 17	-10°C	NA
EGN 3V	Ventilated Cooling Well	NA	44 x 27 x 21	2°C ~ 8°C	3 x GN 1/1
EVRX 1200	Display Counter	NA	48 x 13 x 17	2°C ~ 8°C	5 x GN 1/4
EVRX 1400	Display Counter	NA	56 x 13 x 17	2°C ~ 8°C	6 x GN 1/4
CBR 1-2	Flexdrawer Counter	78	36 x 28 x 23	1°C ~ 4°C / -18°C ~ -21°C	2 x GN 1/1
CBR 1-3	Flexdrawer Counter	116	49 x 28 x 23	1°C ~ 4°C / -18°C ~ -21°C	3 x GN 1/1
CBR 2-2	Flexdrawer Counter	179	36 x 28 x 33	1°C ~ 4°C / -18°C ~ -21°C	4 x GN 1/1
CBR 2-3	Flexdrawer Counter	262	49 x 28 x 33	1°C ~ 4°C / -18°C ~ -21°C	6 x GN 1/1
D3	Blast Chiller & Freezer	139	31 x 32 x 37	1°C ~ 4°C / -18°C ~ -21°C	3 Tray
D5	Blast Chiller & Freezer	169	31 x 32 x 40	3°C ~ -18°C	5 Tray

Specifications, features and colours are subject to change without any notice, due to continuous product development.

All units suitable to work at ambient 38°C

GN Pans are not part of equipment

Authorised Distributor