

Kitchen | Retail | Supermarket | Confectionery
| Ice Machine | Special Product | Cold Room

ELANPRO[®]
The Commercial Refrigeration Experts

Retail



Retail Solutions - Premium Series

Elanpro Flat & Curved Glass Freezers are known for their performance, aesthetics and low power consumption. All curved glass models are available with LED light or Illuminated Canopy with full basket. Flat Glass comes with high insulation and standard / QDI baskets, they are designed to perform at high ambient.



EKG 215 DPG (Canopy Optional)



EKG 626 DLG



EKG 205 AG / 305 AG / 405 AG / 505 AG



EKG 650 G

Key Features : Glass Top

- ❖ High performing cooling systems
- ❖ High insulations
- ❖ Low power consumptions
- ❖ Heavy duty castors

Key Features : Hard Top

- ❖ Low power consumption
- ❖ High insulation
- ❖ Castors for easy mobility



ECF 105 G



EF 305 G



EF 455 G / 555 G



EF 825 G

Retail Solutions - Classic Series



PCF 110/200



EF 335 DDG



EF 435 DDG



EF 535 DG

TECHNICAL SPECIFICATION

DESCRIPTION	EF 76	ECF 105G	ECF 205G	EF 305 G / EF 305 GDD	EF 455 G	EF 555 G	EF 825 G	EF 875	EF 335 DDG	EF 435 DDG	EF 535 DG	EF 290	EF 390	EF 315	EF 415	EF 515	PCF 110	PCF 200	
Type	Milk Cooler			Hard Top Freezer								Hard Top Freezer cum Chiller (Combi)					FOW		
Star Rating	NA	NA	NA	4	5	5	5	5	3	4	5	NA	NA	NA	NA	NA	NA	NA	NA
Gross Capacity (Ltr)	76	98	197	283	375	465	757	805	333	442	551	189F+98C	160F+201C	166F+130C	218F+183C	272F+237C	110	200	
Ext. Dim. (WxDxH) (mm)	404 x 610 x 830	550 x 475 x 848	632 x 554 x 848	1100 x 662 x 886	1309 x 693 x 838	1653 x 695 x 842	2415 x 695 x 842	1848 x 857 x 960	1115 x 720 x 845	1395 x 720 x 845	1685 x 720 x 845	1200 x 602 x 866	1309 x 692 x 924	1117 x 736 x 863	1397 x 712 x 864	1701 x 736 x 863	980 x 645 x 825	1035 x 645 x 905	
Baskets	1	1	1	1	2	2	2	1	1	2	2	1	1	2	2	2	NA	NA	
No. of Door	1	1	1	1 / 2	2	2	3	3	2	2	2	2	2	2	2	2	1	2	
Temperature range - °C	2°C ~ 8°C			-18°C ~ -25°C								8°C ~ -25°C / -16°C ~ -28°C					-18°C ~ -28°C		
Energy Cons. - Kwh/yr	290	310	493	767	785	803	1442	1311	1116	1153	1175	NA	NA	NA	NA	NA	NA	NA	
Castors	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	NA	NA	
Lock	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	NA	NA	

DESCRIPTION	EKG 205 AG	EKG 305 AG	EKG 405 AG	EKG 505 AG	EKG 650 G	EKG 215 DPG	EKG 310 DLG	EKG 410 DLG	EKG 415 DLG	EKG 626 DLG
Type	Flat Glass Top Freezer					Curve Glass Top Freezer				
Star Rating	5	5	5	5	5	4	3	4	4	4
Gross Capacity (Ltr)	197	285	363	439	566	169	255	330	333	574
Ext. Dim. (WxDxH) (mm)	816 x 554 x 848	1014 x 694 x 844	1224 x 694 x 844	1434 x 694 x 844	1800 x 675 x 850	785 x 656 x 839	1000 x 649 x 850	1224 x 649 x 850	1225 x 695 x 918	1844 x 694 x 850
Baskets	2 Q3	1 Q3 + 1 Q6	1 Q3 + 1 Q6	1 Q3 + 1 Q6	9	1	4	5	5	9
Temperature range - °C	-16°C ~ -24°C									
Energy Cons. - Kwh/yr	970	1113	1278	1672	2007	920	1460	1553	1321	2336
Castors	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Lock	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes

Note : Due to continuous product development, specifications, features and colours are subject to change without notice.

Q3 = QDI 3 Pocket, Q6 = QDI 6 Pocket

Upright Showcase Chiller & Freezer (Frost Free & Static)



Key Features:

- ❖ Eco-friendly refrigerant
- ❖ LED lighting for better visibility
- ❖ Adjustable shelves
- ❖ Low power consumption
- ❖ High insulation
- ❖ Removable gasket
- ❖ Triple pane heated glass in all freezers
- ❖ Tropicalized for harsh Indian weather conditions
- ❖ Castor & Lock available

TECHNICAL SPECIFICATION

DESCRIPTION	ECG 205	ECG 305	ECG 405	ECG 515	ECG 606	ECG 775	ECG 1075	ECG 1100	ECG 1506	EFGV 375	EFGV 500	EFGV 1000	EFGV 1500
Type	Upright Chiller								Upright Freezer [#]				
Gross Capacity (Ltr)	200	300	400	515	600	700	1000	1000	1500	375	500	1000	1500
Ext. Dim. (WxDxH) (mm)	500 x 578 x 1520	560 x 618 x 1674	645 x 618 x 1914	680 x 690 x 2010	850 x 720 x 2205	1090 x 750 x 2050	1255 x 750 x 2050	1200 x 710 x 1940	1800 x 590 x 2015	600 x 610 x 1750	680 x 700 x 2020	1370 x 700 x 1990	2058 x 722 x 1982
Shelves	3	4	4	4	5	8	8	10	15	4	4	10	15
No. of Door/Type	1/Glass	1/Glass	1/Glass	1/Glass	1/Glass	2/Glass	2/Glass	2/Glass	3/Glass	1/Glass	1/Glass	2/Glass	3/Glass
Temperature Range - °C	2°C ~ 10°C								-16°C ~ -20°C				
Digital Controller	NA	NA	NA	Yes	NA	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Input Power Watts	124	124	160	260	325	410	420	530	600	760	760	1011	1154

Electricals : 220V, 50Hz, Single phase specifications, features and colours are subject to change without any notice, due to continuous product development.

[#] At 32°C ambient



ELANPRO[®]
The Commercial Refrigeration Experts
@elanprogroup @elanprogroup Elan Professional



Customer Care : +91-88823 02532 • Email : care@elanpro.net
Email : enquiry@elanpro.net • Website : www.elanpro.net
E-Waste Helpline : 1800 258 2550, e-waste@elanpro.net



SCAN TO CONNECT: 8010803166

Authorised Distributor